



AB5 Base Jack

Specifications

The AB5 Base Jack offers:

- Strength
- Quality
- Efficiency

AB5 Base Jacks are designed as a falsework application, and are generally used on ground works applications.

AB5 Base Jacks are manufactured from a rolled thread tubular process, which SCP pioneered throughout the scaffold industry.

The rolled thread tubular process offers an approximate weight reduction of 50%, but maintains and exceeds the strength of a solid cut bar as non of the material is cut away. This improves handling and lowers transport costs.

All SCP Jacks are manufactured in accordance with ISO 9001:2000 quality system accreditation.

PRODUCT CODE	DESCRIPTION	LENGTH (mm)		WEIGHT (kgs)
		Closed	Open	
8-220-STAN-200	38.1mm x 4.88mm x 2000mm Overall 4TPI Acme 150mm x 150mm x 6mm Base Plate GB1 Double Wing Collar	40	167	2.5



Technical Information

- Safe working load: 6000kg (concentric loading).
- Thread: 4TPI Acme BS4360/50C.
- Base Plate: 150 x 150 x 6mm to BS4360/43A.
- AB5 Base Jacks are independently tested and comply with Metal Scaffolding Standards BS1139 and EN74.
- Finish: Bright Zinc Plated.

High specification products designed to last...

1 Station Court, Girton Road, Cannock, Staffordshire WS11 0EJ
Tel: 01543 467 800 | Fax: 01543 467 993 | Email: acp@scpburton.co.uk

